


TRANSIENT VOLTAGE SUPPRESSOR

VRD

VRD is a transient voltage suppressor used for protecting electric circuits from surge voltage and thus preventing breakdown. VRD has superior surge suppression characteristics, such as extremely fast response time, very low clamping voltage, and high surge capacity. Unlike metal oxide varistors, VRD does not have characteristics to change with surge variations within the rated capacity. This feature comprises another superior characteristics of the VRD as a transient voltage suppressors.



Part number

Z2 033 U - 52Z	
Z2	: Rated electricity 1.0W
033	: Break down voltage
U	: Uni-Polar
52Z	: Axial taping winding type
	: Axial taping relay type
	: Radial form taping type
	: individually packed in a bag
	: Bi-Polar
	: Rated electricity 2.0W
	: Rated electricity 0.5W (reverse blocking type)

Electrical characteristics

Figure 1 shows the electrical characteristics. Bipolar type has almost symmetrical breakdown Voltage (V_B) The reverse breakdown voltage of the ZD type is 200 Volts or more at 10 μ A DC.




Fig 1

Taping

One of standard taping is as shown in Figure.




Fig 2

Taping qty

Part series	Taping method	Qty(pcs)	
Z2,Z2U	Axial taping	reel type	5,000
		winding type	2,000
	Radial taping	winding type	2,000
Z6,Z6U	Axial taping	reel type	2,500
		winding type	1,000

Surge capability

Allowable surge capability (P_{PPM}) is determined by the following equation:

$$P_{PPM} = I_{PPM} \times V_C$$

I_{PPM} : Rated peak impulse current

V_C : clamping voltage

The allowable surge capability (Rated peak impulse power dissipation P_{PPM}) of VRD is shown in following Figure 3 and the surge capability derating characteristics are shown in Figure 6.




Fig 3

Surge waveform

There are many types of surge waveform depending on the source of the surge. For the VRD surge suppression characteristics test, the EXP waveform shown below is used. The EXP waveform is shown as t_a/t_b depending on the time width, however 10/1000 waveform is used as the standard test waveform.






Fig 4

Surge suppression characteristics

When EXP waveform is applied, the surge suppression waveform shown in the figure 5 can be observed.






Power derating



Z2 type VRD has bipolar or unipolar electrical characteristics.

Maximum ratings
 Rated peak impulse power dissipation :500 W (10/1000 μ s)
 6.00 kW (8/20 μ s)
 Rated average power dissipation:1W
 Operating and storage temperature : -40°C to 125°C

Symbol mark



Part No.		Stand-off voltage V_s V	Stand-by current I_D μA	Breakdown voltage $V_{(BR)}$ V	Pulsed d.c. test current I_T mA	Clamping Voltage & Rated peak impulse current				Temperature coefficient (TYP)	Capacitance (TYP) pF
Bi-polar type	Uni-polar type					10/1000 μ s		8/20 μ s			
						V_C V	I_{PPM} A	V_C V	I_{PPM} A		
Z2008	—	6.63	500	7.38-9.02	10	12.5	40.0	16.3	372	0.045	1200
—	Z2008U			7.38-9.02							
Z2010	—	8.10	100	9.00-11.0	1	15.0	33.4	19.5	311	0.055	950
—	Z2010U			9.00-11.0							
Z2012	—	9.72	20	10.8-13.2	1	17.3	28.9	22.7	267	0.066	790
—	Z2012U			10.8-13.2							
Z2015	—	12.1	20	13.5-16.5	1	22.0	22.7	28.4	213	0.075	640
—	Z2015U			13.5-16.5							
Z2018	—	14.5	20	16.2-19.8	1	26.5	18.8	34.0	178	0.079	520
—	Z2018U			16.2-19.8							
Z2022	—	17.8	20	19.8-24.2	1	31.9	15.7	41.2	147	0.082	420
—	Z2022U			19.8-24.2							
Z2027	—	21.8	20	24.3-29.7	1	39.1	12.8	50.5	120	0.085	340
—	Z2027U			24.3-29.7							
Z2033	—	26.8	20	29.7-36.3	1	47.7	10.5	61.7	98.2	0.087	280
—	Z2033U			29.7-36.3							
Z2039	—	31.6	20	35.1-42.9	1	56.4	8.86	73.0	83.0	0.090	240
—	Z2039U			35.1-42.9							
Z2047	—	38.1	5	42.3-51.7	1	67.8	7.37	88.0	68.9	0.092	200
—	Z2047U			42.3-51.7							
Z2056	—	45.4	5	50.4-61.6	1	80.5	6.21	105.0	57.7	0.094	160
—	Z2056U			50.4-61.6							
Z2068	—	55.1	5	61.2-74.8	1	98.0	5.10	127.0	47.7	0.096	130
—	Z2068U			61.2-74.8							
Z2082	—	66.4	5	73.8-90.2	1	118.0	4.24	153.0	39.6	0.099	110
—	Z2082U			73.8-90.2							
Z2100	—	81.0	5	90.0-110	1	144.0	3.47	187.0	32.4	0.101	90
—	Z2100U			90.0-110							
Z2120	—	97.2	5	108-132	1	173.0	2.89	222.0	27.3	0.103	75
—	Z2120U			108-132							
Z2150	—	121.0	5	135-165	1	215.0	2.32	277.0	21.9	0.105	60
—	Z2150U			135-165							
Z2180	—	146.0	5	162-198	1	258.0	1.94	333.0	18.2	0.106	49
—	Z2180U			162-198							

NOTE: Nonsuffix:bi-polar, suffix"U" : uni-polar.

Part No.		Stand-off voltage V _s V	Stand-by current I _D μA	Breakdown voltage V _(BR) V	Pulsed d.c. test current I _T mA	Clamping Voltage & Rated peak impulse current				Max. temp. coef. %/°C	Capacitance (TYP) pF
Bi-polar type	Uni-polar type					10/1000μs		8/20μs			
						V _C V	I _{PPM} A	V _C V	I _{PPM} A		
-	Z6008U	6.63	500	7.38-9.02	10	12.5	120	16.3	1120	0.063	14600
Z6010	-	8.10	200	9.00-11.0	1	15.0	100	19.5	933	0.055	5600
-	Z6010U		50	9.00-11.0						0.071	11200
Z6012	-	9.72	10	10.8-13.2	17.3	86.7	22.7	802	0.066	4400	
-	Z6012U			10.8-13.2					0.074	8800	
Z6015	-	12.1	10	13.5-16.5	22.0	68.2	28.4	641	0.075	3300	
-	Z6015U			13.5-16.5					0.079	6600	
Z6018	-	14.5	10	16.2-19.8	26.5	56.6	34.0	535	0.079	2700	
-	Z6018U			16.2-19.8					0.083	5400	
Z6022	-	17.8	10	19.8-24.2	31.9	47.0	41.2	442	0.082	2400	
-	Z6022U			19.8-24.2					0.086	4400	
Z6027	-	21.8	10	24.3-29.7	39.1	38.4	50.5	360	0.085	1700	
-	Z6027U			24.3-29.7					0.089	3300	
Z6033	-	26.8	10	29.7-36.3	47.7	31.4	61.7	295	0.087	1400	
-	Z6033U			29.7-36.3					0.092	2800	
Z6039	-	31.6	10	35.1-42.9	56.4	26.6	73.0	249	0.090	1200	
-	Z6039U			35.1-42.9					0.095	2400	
Z6047	-	38.1	5	42.3-51.7	67.8	22.1	88.0	207	0.092	1000	
-	Z6047U			42.3-51.7					0.097	2000	
Z6056	-	45.4	5	50.4-61.6	80.5	18.6	105.0	173	0.094	850	
-	Z6056U			50.4-61.6					0.099	1700	
Z6068	-	55.1	5	61.2-74.8	98.0	15.3	127.0	143	0.096	720	
-	Z6068U			61.2-74.8					0.100	1440	
Z6082	-	66.4	5	73.8-90.2	118.0	12.7	153.0	119	0.099	610	
-	Z6082U			73.8-90.2					0.102	1220	
Z6100	-	81.0	5	90.0-110	144.0	10.4	187.0	97.3	0.101	520	
-	Z6100U			90.0-110					0.104	1040	
Z6120	-	97.2	5	108-132	173.0	8.67	222.0	82.0	0.103	440	
-	Z6120U			108-132					0.106	880	
-	Z6150U	121.0	5	135-165	215.0	6.98	277.0	65.7	0.107	720	

NOTE : Nonsuffix : Bi-polar, suffix "U" : Uni-polar.

Z6 type VRD has bipolar or unipolar electrical characteristics.


Maximum ratings

Rated peak impulse power dissipation
:1.5kW(10/1000μs)
18.0kW(8/20μs)

Rated average power dissipation:2W

Operating and storage temperature
:-40°C to 125°C

Symbol mark



VRD part No.	Stand-off voltage V _s V	Stand-by current I _D μA	Breakdown voltage V _(BR) V	Pulsed d.c. test current I _T mA	Clamping Voltage & Rated peak impulse current				Max. temp. coef. %/°C	Capacitance (TYP) pF
					10/1000μs		8/20μs			
					V _C V	I _{PPM} A	V _C V	I _{PPM} A		
ZD015	11.4	10	12.8-17.2	1	24.0	10.4	31.0	96.7	0.075	31.5
ZD018	13.7		15.3-20.7		28.0	8.93	36.0	83.3	0.079	31.0
ZD022	16.8	5	18.7-25.3	1	33.2	7.53	43.0	69.7	0.082	29.0
ZD027	20.6		23.0-31.0		40.0	6.25	52.0	57.7	0.085	28.2
ZD033	25.2	5	28.1-37.9	1	48.6	5.14	63.0	47.6	0.087	27.2
ZD039	29.8		33.2-44.8		57.4	4.35	74.0	40.5	0.090	26.3
ZD047	35.9	5	40.0-54.0	1	68.5	3.65	89.0	33.7	0.092	25.0
ZD056	42.8		47.6-64.4		81.0	3.08	106.0	28.6	0.094	24.1
ZD068	52.0	5	57.8-78.2	1	98.0	2.55	127.0	23.8	0.096	22.0


Low capacitance type

Maximum ratings

Reverse voltage:200 VDC
Rated peak impulse power dissipation
:250 W(10/1000μs)
3.00 kW(8/20μs)


Rated average power dissipation:500 mW
Operating and storage temperature
:-40°C to 125°C

Symbol mark




SMD VRD


Part number



Dimensions




Marking



	Rating
Rated average power dissipation	1.0W
Rated peak impulse power dissipation	300W(10/1000 μ s)
	1200W(1.2/50 μ s)
	2000W(8/20 μ s)
Storage temp. range	-40°C~150°C

Taping



A	B	W	F	E	P ₁
3.0 ±0.1	5.2 ±0.1	12.0 ±0.3	5.5 ±0.05	1.75 ±0.1	4.0 ±0.1
P ₂	P ₀	phi D ₀	phi D ₁	T ₁	T ₂
2.0 ±0.1	4.0 ±0.1	1.5 +0.1 -0	1.5 +0.2 -0	0.3 ±0.05	(2.6)

Unit (mm)

Specifications

ZS type

Part No.	Breakdown voltage	Stand-off voltage	Stand-by current	Maximum clamping voltage & Maximum peak pulse current				Temperature coefficient (TYP)	Capacitance (TYP)			
				V _(BR)	V _s	I _L max	V _{Cmax} /1PPM					
							10/1000 μ s			8/20 μ s		
							V			A	V	A
ZS1012	12(10.8~13.2)	9.72	10	17.3	17.3	22.4	89.3	0.066	551			
ZS1015	15(13.5~16.5)	12.1	5	22.0	13.6	28.5	70.2	0.075	465			
ZS1018	18(16.2~19.8)	14.5		26.5	11.3	34.4	58.1	0.079	376			
ZS1022	22(19.8~24.2)	17.8		31.9	9.40	41.4	48.3	0.082	299			
ZS1027	27(24.3~29.7)	21.8		39.1	7.67	50.7	39.4	0.085	248			
ZS1033	33(29.7~36.3)	26.8		47.7	6.29	61.8	32.4	0.087	198			
ZS1039	39(35.1~42.9)	31.6		56.4	5.32	73.1	27.4	0.090	164			
ZS1047	47(42.3~51.7)	38.1		67.8	4.42	88.0	22.7	0.092	137			

ZS-U type

Part No.	Breakdown voltage	Stand-off voltage	Stand-by current	Maximum clamping voltage & Maximum peak pulse current				Temperature coefficient (TYP)	Capacitance (TYP)			
				V _(BR)	V _s	I _L max	V _{Cmax} /1PPM					
							10/1000 μ s			8/20 μ s		
							V			A	V	A
ZS1012U	12(10.8~13.2)	9.72	10	17.3	17.3	22.4	89.3	0.066	1,102			
ZS1015U	15(13.5~16.5)	12.1	5	22.0	13.6	28.5	70.2	0.075	929			
ZS1018U	18(16.2~19.8)	14.5		26.5	11.3	34.4	58.1	0.079	751			
ZS1022U	22(19.8~24.2)	17.8		31.9	9.40	41.4	48.3	0.082	598			
ZS1027U	27(24.3~29.7)	21.8		39.1	7.67	50.7	39.4	0.085	497			
ZS1033U	33(29.7~36.3)	26.8		47.7	6.29	61.8	32.4	0.087	395			
ZS1039U	39(35.1~42.9)	31.6		56.4	5.32	73.1	27.4	0.090	328			
ZS1047U	47(42.3~51.7)	38.1		67.8	4.42	88.0	22.7	0.092	274			

ZS-D type

Part No.	Breakdown voltage	Stand-off voltage	Stand-by current	Maximum clamping voltage & Maximum peak pulse current				Temperature coefficient (TYP)	Capacitance (TYP)			
				V _(BR)	V _s	I _L max	V _{Cmax} /1PPM					
							10/1000 μ s			8/20 μ s		
							V			A	V	A
ZS1012D	12(10.8~13.2)	9.72	10	17.3	17.3	22.4	89.3	0.066	30.2			
ZS1015D	15(13.5~16.5)	12.1	5	22.0	13.6	28.5	70.2	0.075	29.1			
ZS1018D	18(16.2~19.8)	14.5		26.5	11.3	34.4	58.1	0.079	28.2			
ZS1022D	22(19.8~24.2)	17.8		31.9	9.40	41.4	48.3	0.082	27.3			
ZS1027D	27(24.3~29.7)	21.8		39.1	7.67	50.7	39.4	0.085	26.4			
ZS1033D	33(29.7~36.3)	26.8		47.7	6.29	61.8	32.4	0.087	25.5			
ZS1039D	39(35.1~42.9)	31.6		56.4	5.32	73.1	27.4	0.090	24.8			
ZS1047D	47(42.3~51.7)	38.1		67.8	4.42	88.0	22.7	0.092	24.0			